



## SAFETY DATA SHEET

Revision date 28-Oct-2015

Version 2

### Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name** FL-8 PINK 6UC  
**Product Code** 400.0002208.076  
**UN/ID no** UN1950  
**Recommended Use** Aerosol, Paint

#### Details of the supplier of the safety data sheet

*See section 16 for more information*

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

Valspar Industries, Inc.  
1915 Second St. W.  
Cornwall, Ontario K6H 5R6

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

**Emergency telephone number** 1-888-345-5732

### Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### HAZARD STATEMENTS

Flammable aerosol Contains gas under pressure; may explode if heated  
May cause drowsiness or dizziness May be fatal if swallowed and enters airways

#### WHMIS Hazard Class

B5 - Flammable aerosol  
A Compressed gases  
D2B - Toxic materials



**Signal word**

**DANGER**

#### PREVENTION

Use only outdoors or in a well-ventilated area Do not spray on an open flame or other ignition source Avoid breathing dust/fume/gas/mist/vapors/spray Pressurized container: Do not pierce or burn, even after use

**Product Code 400.0002208.076**

Page 1 / 9

WPNA - CANADA WHMIS SDS

## RESPONSE

Get medical advice/attention if you feel unwell

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Skin

Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention

### Inhalation

Call a POISON CENTER or doctor/physician if you feel unwell IF INHALED: Remove person to fresh air and keep comfortable for breathing

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

## STORAGE

Do not expose to temperatures exceeding 122 °F (50 °C) Store locked up Protect from sunlight. Store in a well-ventilated place  
Store in a well-ventilated place

## DISPOSAL

Dispose of contents/containers in accordance with local regulations

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                               | CAS No     | weight-% |
|---------------------------------------------|------------|----------|
| Solvent naphtha, petroleum, light aliphatic | 64742-89-8 | 25 - 50  |
| Barium sulfate                              | 7727-43-7  | 10 - 25  |
| Propane                                     | 74-98-6    | 10 - 25  |
| Butane                                      | 106-97-8   | 10 - 25  |
| n-Butyl acetate                             | 123-86-4   | 3 - 5    |

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### General advice

Get medical advice/attention if you feel unwell

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Skin Contact

Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention

#### Inhalation

Call a POISON CENTER or doctor/physician if you feel unwell IF INHALED: Remove person to fresh air and keep comfortable for breathing

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

### Most important symptoms and effects, both acute and delayed

#### Symptoms

No information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physicians

Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

Product Code 400.0002208.076

Page 2 / 9

WPNA - CANADA WHMIS SDS

|                                  |                           |
|----------------------------------|---------------------------|
| <b>Flammable properties</b>      | Flammable liquid.         |
| <b>flash point</b>               | -31 °F / -35 °C           |
| <b>Upper flammability limit:</b> | No information available  |
| <b>Lower flammability limit:</b> | No information available  |
| <b>Autoignition temperature</b>  | No information available  |
| <b>Explosion data</b>            |                           |
| Sensitivity to Mechanical Impact | No information available. |
| Sensitivity to Static Discharge  | No information available. |

#### **Suitable extinguishing media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

#### **Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

#### **Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

#### **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## **Section 7: HANDLING AND STORAGE**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse.

### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Protect from sunlight. Store in a well-ventilated place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical Name               | ACGIH TLV                                                                                                                        | Alberta                                                                                    | British Columbia                                      | Ontario TWA                   | Quebec                                                                                     | OSHA PEL                                                                                   |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Barium sulfate<br>7727-43-7 | TWA: 5 mg/m <sup>3</sup><br>inhalable fraction,<br>particulate matter<br>containing no<br>asbestos and <1%<br>crystalline silica | TWA: 10 mg/m <sup>3</sup>                                                                  | TWA: 10 mg/m <sup>3</sup><br>TWA: 3 mg/m <sup>3</sup> | TWA: 10 mg/m <sup>3</sup>     | TWA: 10 mg/m <sup>3</sup><br>TWA: 5 mg/m <sup>3</sup>                                      | TWA: 15 mg/m <sup>3</sup><br>total dust<br>TWA: 5 mg/m <sup>3</sup><br>respirable fraction |
| Propane<br>74-98-6          | TWA: 1000 ppm                                                                                                                    | TWA: 1000 ppm                                                                              | TWA: 1000 ppm                                         | TWA: 1000 ppm                 | TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>                                               | TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>                                               |
| Butane<br>106-97-8          | STEL: 1000 ppm                                                                                                                   | TWA: 1000 ppm                                                                              | TWA: 600 ppm<br>STEL: 750 ppm                         | TWA: 800 ppm                  | TWA: 800 ppm<br>TWA: 1900 mg/m <sup>3</sup>                                                |                                                                                            |
| n-Butyl acetate<br>123-86-4 | STEL: 200 ppm<br>TWA: 150 ppm                                                                                                    | TWA: 150 ppm<br>TWA: 713 mg/m <sup>3</sup><br>STEL: 200 ppm<br>STEL: 950 mg/m <sup>3</sup> | TWA: 20 ppm                                           | TWA: 150 ppm<br>STEL: 200 ppm | TWA: 150 ppm<br>TWA: 713 mg/m <sup>3</sup><br>STEL: 200 ppm<br>STEL: 950 mg/m <sup>3</sup> | TWA: 150 ppm<br>TWA: 710 mg/m <sup>3</sup>                                                 |

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection

#### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                              |                          |
|------------------------------|--------------------------|
| Physical state               | Aerosol                  |
| Appearance                   | No information available |
| Odor                         | Solvent                  |
| Color                        | pink                     |
| Odor Threshold               | No information available |
| pH value                     | No information available |
| Melting point/freezing point | No information available |

Product Code 400.0002208.076

Page 4 / 9

WPNA - CANADA WHMIS SDS

|                                      |                                  |
|--------------------------------------|----------------------------------|
| <b>Boiling point / boiling range</b> | No information available °C / °F |
| <b>flash point</b>                   | -35 °C / -31 °F                  |
| <b>evaporation rate</b>              | No information available         |
| <b>Flammability (solid, gas)</b>     | No information available         |
| <b>Flammability Limit in Air</b>     |                                  |
| <b>Upper flammability limit:</b>     | No information available         |
| <b>Lower flammability limit:</b>     | No information available         |
| <b>Vapor Pressure</b>                | No information available         |
| <b>vapor density</b>                 | No information available         |
| <b>Density (lbs per US gallon)</b>   | 7.14                             |
| <b>specific gravity</b>              | .86                              |
| <b>Solubility(ies)</b>               | Not Determined                   |
| <b>Partition coefficient</b>         | No information available         |
| <b>Autoignition temperature</b>      | No information available         |
| <b>Decomposition temperature</b>     | No information available         |
| <b>Kinematic viscosity</b>           | No information available         |
| <b>Dynamic viscosity</b>             | No information available         |

#### Other information

### Section 10: STABILITY AND REACTIVITY

|                                           |                                                                                                           |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Stability</b>                          | Stable under normal conditions.                                                                           |
| <b>Incompatible materials</b>             | Strong oxidizing agents.                                                                                  |
| <b>Conditions to avoid</b>                | Heat, flames and sparks.                                                                                  |
| <b>Hazardous Decomposition Products</b>   | Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Nitrogen oxides (NO <sub>x</sub> ). Oxides of sulfur. |
| <b>Possibility of Hazardous Reactions</b> | None under normal processing.                                                                             |
| <b>Hazardous polymerization</b>           | None under normal processing.                                                                             |

### Section 11: TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

#### Information on likely routes of exposure

##### **Eye contact**

Not applicable

##### **Skin Contact**

Not applicable

##### **Ingestion**

May be fatal if swallowed and enters airways

##### **Inhalation**

May cause drowsiness or dizziness

#### Numerical measures of toxicity - Component Information

| Chemical Name                               | Oral LD50             | Dermal LD50              | Inhalation LC50                    |
|---------------------------------------------|-----------------------|--------------------------|------------------------------------|
| Solvent naphtha, petroleum, light aliphatic | -                     | = 3000 mg/kg ( Rabbit )  | -                                  |
| Barium sulfate                              | -                     | -                        | -                                  |
| Propane                                     | -                     | -                        | = 658 mg/L ( Rat ) 4 h             |
| Butane                                      | -                     | -                        | = 658 g/m <sup>3</sup> ( Rat ) 4 h |
| n-Butyl acetate                             | = 14.13 mg/kg ( Rat ) | > 17600 mg/kg ( Rabbit ) | = 390 ppm ( Rat ) 4 h              |

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

|                                  |                |
|----------------------------------|----------------|
| <b>Skin corrosion/irritation</b> | Not applicable |
|----------------------------------|----------------|

**Product Code 400.0002208.076**

Page 5 / 9

WPNA - CANADA WHMIS SDS

|                                                    |                                   |
|----------------------------------------------------|-----------------------------------|
| Serious eye damage/eye irritation                  | Not applicable                    |
| Skin sensitization                                 | Not applicable                    |
| Respiratory sensitization                          | Not applicable                    |
| Germ cell mutagenicity                             | Not applicable                    |
| Carcinogenicity                                    | Not applicable                    |
| Reproductive Toxicity                              | Not applicable                    |
| Specific target organ toxicity (single exposure)   | May cause drowsiness or dizziness |
| Specific target organ toxicity (repeated exposure) | Not applicable                    |
| Aspiration hazard                                  | Not applicable                    |

## Section 12: ECOLOGICAL INFORMATION

### Ecotoxicity

May cause long-term adverse effects in the aquatic environment.

Marine pollutant This material meets the definition of a marine pollutant

Environmental precautions Prevent product from entering drains.

| Chemical Name                               | Algae/aquatic plants                                         | Fish                                                                                               | Crustacea |
|---------------------------------------------|--------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-----------|
| Solvent naphtha, petroleum, light aliphatic | = 4700 mg/L <i>Pseudokirchneriella subcapitata</i> 72 h EC50 | -                                                                                                  | -         |
| Barium sulfate                              | -                                                            | -                                                                                                  | -         |
| Propane                                     | -                                                            | -                                                                                                  | -         |
| Butane                                      | -                                                            | -                                                                                                  | -         |
| n-Butyl acetate                             | = 674.7 mg/L <i>Desmodemus subspicatus</i> 72 h EC50         | = 100 mg/L <i>Lepomis macrochirus</i> 96h LC50<br>17 - 19 mg/L <i>Pimephales promelas</i> 96h LC50 | -         |

Persistence and degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

| Chemical Name                               | Partition Coefficient (n-octanol/water) |
|---------------------------------------------|-----------------------------------------|
| Solvent naphtha, petroleum, light aliphatic | -                                       |
| Barium sulfate                              | -                                       |
| Propane                                     | 2.3                                     |
| Butane                                      | 2.89                                    |
| n-Butyl acetate                             | 1.81                                    |

## Section 13: DISPOSAL CONSIDERATIONS

Waste from residues/unused products Disposal should be in accordance with applicable regional, national and local laws and regulations

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal.

## Section 14: TRANSPORT INFORMATION

|                      |                      |                       |                       |
|----------------------|----------------------|-----------------------|-----------------------|
| UN/ID no             | <u>TDG</u><br>UN1950 | <u>IMDG</u><br>UN1950 | <u>IATA</u><br>UN1950 |
| Proper shipping name | Aerosols             | Aerosols              | Aerosols              |

Product Code 400.0002208.076

Page 6 / 9

WPNA - CANADA WHMIS SDS

|                             |                                                          |     |     |
|-----------------------------|----------------------------------------------------------|-----|-----|
| <b>Hazard Class</b>         | 2.1                                                      | 2.1 | 2.1 |
| <b>Packing Group</b>        |                                                          |     |     |
| <b>Environmental hazard</b> | Yes                                                      |     |     |
| <b>Marine pollutant</b>     | This material meets the definition of a marine pollutant |     |     |
| <b>Marine pollutant</b>     | Solvent naphtha, petroleum, light aliphatic              |     |     |
| <b>Special Provisions</b>   |                                                          |     |     |

EmS-No  
F-D, S-U

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

## Section 15: REGULATORY INFORMATION

### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR**

### WHMIS Hazard Class

B5 - Flammable aerosol

A - Compressed gases

D2B - Toxic materials



| Chemical Name                               | Canada - 2013 NPRI (National Pollutant Release Inventory) |
|---------------------------------------------|-----------------------------------------------------------|
| Solvent naphtha, petroleum, light aliphatic | Part 5, Other Groups and Mixtures                         |
| Propane                                     | Part 5, Individual Substances                             |
| Butane                                      | Part 5, Isomer Groups Part 4 Substance                    |
| n-Butyl acetate                             | Part 5, Individual Substances                             |

### GHS - Classification

|                                                  |               |
|--------------------------------------------------|---------------|
| Specific target organ toxicity (single exposure) | Category 3    |
| Aspiration toxicity                              | Category 1    |
| Flammable aerosols                               | Category 2    |
| Gases under pressure                             | Liquefied gas |

### Label elements



Signal word

**DANGER**

### HAZARD STATEMENTS

Flammable aerosol

Contains gas under pressure; may explode if heated

**Product Code 400.0002208.076**

Page 7 / 9

WPNA - CANADA WHMIS SDS

May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways

#### PREVENTION

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

#### RESPONSE

Get medical advice/attention if you feel unwell.

##### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Skin

Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

##### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

##### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 122 °F (50 °C).

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

Propellant is classified as a simple asphyxiant if released in large quantities: May displace oxygen and cause rapid suffocation.

#### OTHER HAZARDS

Toxic to aquatic life with long lasting effects.

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

### Section 16: OTHER INFORMATION

#### HMIS

|                     |   |
|---------------------|---|
| Health hazards      | 3 |
| Flammability        | 4 |
| Physical hazards    | 0 |
| Personal Protection | X |

#### Supplier Address

|                                                                     |                                                                                    |                                                                                          |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Valspar Consumer Headquarters                                       | The Valspar Corporation<br>4999 36th St.<br>Grand Rapids, MI 49512<br>800-253-3957 | Valspar Plasti-Kote<br>1636 Shawsone Dr.<br>Mississauga, Ontario L4W 1N7<br>905-671-8333 |
| 8725 W. Higgins Rd. Suite 1000<br>Chicago, IL 60631<br>773-628-5500 |                                                                                    |                                                                                          |

**Prepared By** Product Stewardship

**Revision date** 28-Oct-2015

**Revision Note** No information available

#### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**Product Code 400.0002208.076**

Page 8 / 9

WPNA - CANADA WHMIS SDS

**End of Safety Data Sheet**