Reviewed on 06/21/2017

1 Identification

· Product identifier

Printing date 03/21/2018

· Trade name: 61993 Custom Fill Aerosol

· Article number: 61993

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225

· Information department:

cust\_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



GHS07

Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure -

H336 May cause drowsiness or dizziness.

Category 3

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS04

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone

butanone

(Contd. on page 2)



Trade name: 61993 Custom Fill Aerosol

(Contd. of page 1)

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)

**HEALTH** 

Health = 2Fire = 4

REACTIVITY 3 Reactivity = 3

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:			
67-64-1 acetone	40-70% w/w		
74-98-6 propane	10-30% w/w		
78-93-3 butanone	≥5-<10% w/w		

(Contd. on page 3)

Trade name: 61993 Custom Fill Aerosol

4 First aid measures

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

(Contd. on page 4)



Trade name: 61993 Custom Fill Aerosol

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot$  *Specific end use*(s) *No further relevant information available.*

## 8 Exposure controls/Personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

### · Components with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

EL Short-term value: 500 ppm Long-term value: 250 ppm EV Short-term value: 750 ppm

Long-term value: 500 ppm

#### 74-98-6 propane

EL Long-term value: 1000 ppm EV Long-term value: 1,000 ppm revoked as of 01/01/18

#### 78-93-3 butanone

EL Short-term value: 100 ppm Long-term value: 50 ppm

EV Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm

#### 763-69-9 ethyl 3-ethoxypropionate

EV Long-term value: 300 mg/m<sup>3</sup>, 50 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)

SEM

Printing date 03/21/2018 Reviewed on 06/21/2017

Trade name: 61993 Custom Fill Aerosol

· Eye protection: Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· Information on	ı basic	physical	l and	chemical	properties

· General Information

· Appearance:

Form: Aerosol

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

· Flash point: -97 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 465 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1.7 Vol %

 Upper:
 13 Vol %

· Vapor pressure at 20 °C: 8,300 hPa

Density at 20 °C: 0.69578 g/cm³
Relative density Not determined.

Vapor density Not determined.
Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

Organic solvents: 100.0 %

(Contd. on page 6)

Trade name: 61993 Custom Fill Aerosol

	(Contd. of page
VOC content:	35.00 % 569.6 g/l / 4.75 lb/gl
Solids content:  Other information	0.0% No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
67-64-1 acetone			
Oral	LD50	5,800 mg/kg (rat)	
		20,000 mg/kg (rabbit)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)



Trade name: 61993 Custom Fill Aerosol

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

		_
TINI	A7	mhor

· DOT, TDG, IMDG, IATA UN1950

· UN proper shipping name

DOT Aerosols, flammable
 TDG 1950 Aerosols
 IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- $\cdot DOT$



· Class 2.1

Label 2.1

· TDG (Transport dangerous goods):



· Class 2 5F Gases

· Label 2.

(Contd. on page 8)

Trade name: 61993 Custom Fill Aerosol

(Contd. of page 7) · IMDG, IATA 2.1 · Class · Label 2.1 · Packing group · DOT, TDG, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Gases · EMS Number: F-D,S-U· Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: · Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code *Not applicable.* · Transport/Additional information:  $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg · Remarks ORM-D 49CFR 173-150,156,306  $\cdot TDG$ · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity  $\cdot$  IMDG · Limited quantities (LQ) 1LCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity UN 1950 AEROSOLS, 2.1 · UN "Model Regulation":

CA ·

Trade name: 61993 Custom Fill Aerosol

(Contd. of page 8)

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3 butanone

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

67-64-1 acetone

78-93-3 butanone

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

02 GHS04

GHS04 GHS

- · Signal word Danger
- · Hazard-determining components of labeling:

acetone

butanone

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

*P251* Do not pierce or burn, even after use.

*P261* Avoid breathing dust/fume/gas/mist/vapours/spray.

*P264 Wash thoroughly after handling.* 

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a poison center/doctor if you feel unwell.

(Contd. on page 10)



Trade name: 61993 Custom Fill Aerosol

(Contd. of page 9)

*P337+P313* If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/21/2018 / 9
- · Abbreviations and acronyms:

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

· \* Data compared to the previous version altered.

CA