

SAFETY DATA SHEET

According to Canadian Hazardous Products Regulations (HPR) (SOR/2015/17)

SDS #: 087299 BIOSPEC HYD 46

Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

1. IDENTIFICATION

Product identifier

Product name BIOSPEC HYD 46

Other means of identification

Product Code(s) 087299

Number A9S Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Hydraulic oil

Uses advised againstDo not use for any purpose other than the one for which it is intended.

Details of the supplier of the safety data sheet

Supplier TOTAL CANADA INC.

220, LAFLEUR LASALLE, QUEBEC

H8R 4C9

Tel: (514) 595-7579 Fax: (514) 595-5950

Contact Point service HSE

E-mail Address ProductSafety@total.com

Emergency telephone number

Emergency telephone 1-800-463-3955

Company Phone Number 1-866-928-0789 (For Emergencies, call CARECHEM 24/7

Domestic)

1-215-207-0061 (For Emergencies, call CARECHEM 24/7

International)

2. HAZARDS IDENTIFICATION

Classification

The product is not classified as hazardous according to WHMIS

Label elements

The product is not classified as hazardous according to WHMIS



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

Hazard Statements

None

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Other hazards Harmful to aquatic life with long lasting effects

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical nature Vegetable oil based.

Chemical Name	EC-No	CAS-No	Weight %
Distillates (petroleum),	265-156-6	64742-53-6	1<3
hydrotreated light naphthenic			
Succinic anhydride, alkylation products with C12-rich branched olefins from propene oligomerisation, hydrolyzed, esterification products with propylene oxide	943-535-3	^	0.1<1

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated



SDS #: 087299

BIOSPEC HYD 46

Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

clothes and shoes. Wash contaminated clothing before reuse. High pressure jets may

cause skin damage. Take victim immediately to hospital.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or Poison Control Center immediately.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device.

Most important symptoms/effects, acute and delayed

Skin contact Not classified based on available data. May produce an allergic reaction. High pressure

injection of the products under the skin may have very serious consequences even though

no symptom or injury may be apparent.

Eye contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Symptoms No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing MediaDo not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Nitrogen oxides

(NOx). Silicon dioxide.

Explosion Data

Sensitivity to Mechanical Impact
Sensitivity to Static Discharge

None. None.



SDS #: 087299

BIOSPEC HYD 46

Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

Special protective equipment for

fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant

spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or

similar non-combustible materials.

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil

contamination, remove contaminated soil for remediation or disposal, in accordance with

local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe

vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product

contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to Avoid Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m3 (highly refined). .

Legend See section 16

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. Ensure

adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the

recommended equipment.

Individual protection measures, such as personal protective equipment

General Information Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE)

recommendations apply to the product ITSELF. In case of mixtures or formulations, it is

suggested that you contact the relevant PPE suppliers.

Eye/face protection If splashes are likely to occur, wear safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protectionNone under normal use conditions. When workers are facing concentrations above the

exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapor/particulate. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations

governing their choices and uses.



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color amber Physical State @20°C liquid

Odor Petroleum distillates
Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks</u> <u>Method</u>

Not applicable

Melting point/range No information available

Boiling point/boiling range No information available

 Flash point
 245 °C
 ASTM D92

 473 °F
 ASTM D92.

Evaporation rateNo information available

Flammability Limits in Air

upperNo information availableLowerNo information availableVapor PressureNo information available

Vapor density

No information available

 Relative density
 0.920
 @ 15 °C
 ASTM D 1298

 Density
 920 kg/m³
 @ 15 °C
 ASTM D 1298

Water solubility Not applicable

Solubility in other solventsNo information availablelogPowNo information availableAutoignition temperatureNo information available

Decomposition temperatureNo information availableViscosity, kinematic37.5 - 46.5 mm2/s@ 40 °CASTM D 4459.15 mm2/s@ 100 °CASTM D 445

Explosive properties Not explosive Oxidizing Properties Not applicable

Possibility of hazardous reactions None under normal processing

Other information

Specific Gravity 0.920 @ 15 °C ASTM D 1298

Freezing Point No information available

Pour point -22 °C ASTM D 97

10. STABILITY AND REACTIVITY

Reactivity None under normal processing.



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat

and sparks. Take precautionary measures against static discharges.

<u>Incompatible materials</u> Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Nitrogen

oxides (NOx). Silicon dioxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Symptoms No information available.

Skin contact Not classified based on available data. May produce an allergic reaction. High pressure

injection of the products under the skin may have very serious consequences even though

no symptom or injury may be apparent.

Eye contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Oral Not classified based on available data

Dermal Not classified based on available data

Inhalation Not classified based on available data

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	LD50 > 5000 mg/kg (Rat - OECD420)	LD50 > 5000 mg/kg (Rabbit - OECD 402)	LC50 (4h) > 5.53 mg/l (Rat - aerosol - OECD403)
Succinic anhydride, alkylation products with C12-rich branched	LD50 2000 mg/kg bw (rat)	LD50 2000 mg/kg bw (rat)	



SDS #: 087299

BIOSPEC HYD 46

Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

olefins from propene oligomerisation, hydrolyzed, esterification products with		
propylene oxide ^		

Skin corrosion/irritationNot classified based on available data. **Serious eye damage/eye irritation**Not classified based on available data.

Respiratory or skin sensitization Not classified based on available data. Contains sensitizer(s). May produce an allergic

reaction.

Germ cell mutagenicityNot classified based on available data.
Carcinogenicity
Not classified based on available data.

Reproductive toxicity Not classified based on available data.

Target Organ Effects (STOT) None known.

STOT - single exposure
STOT - repeated exposure
Aspiration hazard

Not classified based on available data.
Not classified based on available data.
Not classified based on available data.

12. ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic life with long lasting effects

Acute aquatic toxicity - Product Information

No information available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6		LL50(96h) > 100 mg/l (Pimephales promelas - static - OECD203)	EL50 (48h) > 10000 mg/L (Daphnia magna - static - OECD202)	
Succinic anhydride, alkylation products with C12-rich branched olefins from propene oligomerisation, hydrolyzed, esterification products with propylene oxide	EL50(72h) 67-100 mg/l	LL50(96h) 100 mg/L	EL50(48h) 100 mg/l	

Chronic aquatic toxicity - Product Information

No information available



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

Chronic aquatic toxicity - Component Information

-	Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
			other aquatic invertebrates		microorganisms
Ī	Distillates (petroleum),	NOEL (72h) >= 100 mg/l	NOEL(21d) 10 mg/l		
1	hydrotreated light	(Pseudokirchnerella	(Daphnia magna - semi		
1	naphthenic	subcapitata - static -	static - OECD211)		
L	64742-53-6	OECD201)			

Effects on terrestrial organisms

No information available.

Persistence and degradability

No information available

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow
Succinic anhydride, alkylation products with C12-rich branched olefins	4.65 @ 40°C and pH 3
from propene oligomerisation, hydrolyzed, esterification products with	
propylene oxide	
Λ	

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility

Air Loss by evaporation is limited

Water The product is insoluble and floats on water

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

Waste from residues/unused

products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration. Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when

notifying provincial authorities.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) (SOR/2015/17) and the Safety Data Sheet (SDS) contains all the information required by the HPR

following inventories: Canada (DSL/NDSL) U.S.A. (TSCA)

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPAHealth Hazard 1Flammability 1Instability 0Special hazards -HMISHealth Hazard 1Flammability 1Physical Hazard 0Personal protection X

Revision Date: 2019-03-22

Revision Note *** Indicates updated section

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day



Date of the previous version: 2018-02-27 Revision Date: 2019-03-22 Version 2

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

NTP = National Toxicology Program

Section 8

TWA - Time Weight Average

STEL - Short Term Exposure Limits

+ Sensitizer * Skin designation
C: Carcinogen R: Toxic to reproduction

Ceiling: Ceiling Limit Value

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet