



SAFETY DATA SHEET

According to Canadian Hazardous Products Regulations (HPR) (SOR/2015/17)

SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

1. IDENTIFICATION

Product identifier

Product name FLUIDMATIC MV LV

Other means of identification

Product Code(s) 087443

Number 9RV
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Transmission fluid

Uses advised against Do not use for any purpose other than the one for which it is intended.

Details of the supplier of the safety data sheet

Supplier TOTAL CANADA INC.
220, LAFLEUR
LASALLE, QUEBEC
H8R 4C9
Tel: (514) 595-7579
Fax: (514) 595-5950

Contact Point service HSE

E-mail Address info@total-lub.ca

Emergency telephone number

Emergency telephone 1-800-463-3955
Company Phone Number +1 866 928 0789 (24h/24, 7d/7)
+1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization - Category 1

Label elements

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

**WARNING**

May cause an allergic skin reaction

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves

Precautionary Statements - Response

- Specific treatment (see back on this label)

Skin

IF ON SKIN: Wash with plenty of water and soap
 If skin irritation or rash occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown acute toxicity

76 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Chemical nature Mineral oil of petroleum origin.

Chemical Name	EC-No	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1	64742-54-7	70-<80
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	276-737-9	72623-86-0	1-<3
reaction mass of isomers of:	406-040-9	125643-61-0	1-<2.5

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate			
bis(nonylphenyl)amine	253-249-4	36878-20-3	1-<2.5
Reaction product of alkylthioalcohol and substituted phosphorus compound	424-820-7	^	0.1-<0.25
4,4'-thiodiethylene hydrogen-2-octadecenylsuccinate	299-434-3	93882-40-7	0.1-<0.25

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES**First aid measures for different exposure routes****General advice**

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.

Inhalation

Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.

Ingestion

Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Protection of First-aiders

First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed**Skin contact**

May cause an allergic skin reaction.

Eye contact

Not classified based on available data.

Inhalation

Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion

Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms

No information available.

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Phosphorous oxides. Nitrogen oxides (NO_x).

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Special protective equipment for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to Avoid Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Legend See section 16

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Individual protection measures, such as personal protective equipment

General Information	Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.
Eye/face protection	If splashes are likely to occur, wear safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots.
Hand Protection	Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Respiratory protection	None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapor/particulate. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Appearance	limpid
Color	red
Physical State @20°C	liquid
Odor	Characteristic
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		No information available	
Melting point/range		No information available	
Boiling point/boiling range		No information available	
Flash point		No information available	
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper		No information available	
Lower		No information available	
Vapor Pressure		No information available	

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Vapor density		No information available	
Relative density	0.845	@ 15 °C	ASTM D 1298
Density	845 kg/m ³	@ 15 °C	ASTM D1298
Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	29.8 mm ² /s	@ 40 °C	ASTM D445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	None under normal processing		
<u>Other information</u>			
Freezing Point		No information available	

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	None under normal processing.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	No dangerous reaction known under conditions of normal use.
<u>Conditions to avoid</u>	Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.
<u>Incompatible materials</u>	Strong oxidizing agents.
<u>Hazardous Decomposition Products</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATIONInformation on likely routes of exposure

Symptoms	No information available.
Skin contact	May cause an allergic skin reaction.
Eye contact	Not classified based on available data.
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

Oral Not classified based on available data

Dermal Not classified based on available data

Inhalation Not classified based on available data

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0	LD50 > 5000 mg/kg bw (Rat - OECD TG 401)	LD50 > 2000 mg/kg (Rabbit - OECD 402)	LD50 (4h) > 5.53 mg/l (Rat - OECD 403)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	LD50 > 2000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
bis(nonylphenyl)amine 36878-20-3	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
Reaction product of alkylthioalcohol and substituted phosphorus compound ^	LD50 > 2000 mg/kg bw (rat)	LD50 > 500 mg/kg bw (rabbit)	
4,4'-thiodiethylene hydrogen-2-octadecenylsuccinate 93882-40-7	LD50 > 10000 mg/kg (rat)		

Skin corrosion/irritation Not classified based on available data.
Serious eye damage/eye irritation Not classified based on available data.
Respiratory or skin sensitization May cause an allergic skin reaction.
Germ cell mutagenicity Not classified based on available data.
Carcinogenicity Not classified based on available data.

Reproductive toxicity Not classified based on available data.
Target Organ Effects (STOT) None known.
STOT - single exposure Not classified based on available data.
STOT - repeated exposure Not classified based on available data.
Aspiration hazard Not classified based on available data.

12. ECOLOGICAL INFORMATION

Version HGHS

SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Ecotoxicity

Acute aquatic toxicity - Product Information

No information available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		LL50 (96h) > 100 mg/l (OECD TG 203)	EL50(48h) >1000 mg/l (OECD TG 202)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	EC50 (72h) > 3 mg/l (Scenedesmus sp. - OECD 201)	LC50 (96h) > 74 mg/l (Brachydanio rerio - semi static - OECD 203)	EC50(24h) > 100 mg/l (Daphnia magna - OECD 202)	
bis(nonylphenyl)amine 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)	LC50 (96h) > 100 mg/l (Brachydanio rerio - OECD 203)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	
Reaction product of alkylthioalcohol and substituted phosphorus compound ^	EL50 (72h) 0.31 mg/l (Pseudokirchnerella subcapitata)	CL50 (96h) 1.5 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (24h) 2 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (48h) 1.7 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (72h) 1.6 mg/l (Oncorhynchus mykiss - OECD 203) LL50 (96h) 1.5 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) 0.09 mg/l (Daphnia magna - OECD 202)	
4,4'-thiodiethylene hydrogen-2-octadecenylsuccinate 93882-40-7		LC50(96h) >0.17 mg/l (OECD guideline 203)		

Chronic aquatic toxicity - Product Information

No information available

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0		NOEL (21d) = 10 mg/l (OECD TG 202)	NOELR (14d) > 1000 mg/l (QSAR modelled data)	
Reaction product of alkylthioalcohol and substituted phosphorus compound ^	NOELR (72h) 0.13 mg/l (Pseudokirchnerella subcapitata) NOELR (72h) < 0.13 mg/l (Pseudokirchnerella subcapitata)	NOEC (21d) 0.14 mg/l (Daphnia magna) LOEC (21d) 0.35 mg/l (Daphnia magna) LL50 (21d) 0.22 mg/l (Daphnia magna)		

Effects on terrestrial organisms No information available.**Persistence and degradability**

No information available

Bioaccumulative potential**Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based 72623-86-0	6.1
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	9.2
bis(nonylphenyl)amine 36878-20-3	7.7

Mobility**Soil** Given its physical and chemical characteristics, the product generally shows low soil mobility**Air** Loss by evaporation is limited**Water** The product is insoluble and floats on water

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

Other adverse effects**General Information**

No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment****Waste from residues/unused products**

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration. Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION**TDG** Not regulated**DOT** Not regulated**MEX** Not regulated**ICAO/IATA** Not regulated**IMDG/IMO** Not regulated**ADR/RID** Not regulated**ADN** Not regulated**15. REGULATORY INFORMATION**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) (SOR/2015/17) and the Safety Data Sheet (SDS) contains all the information required by the HPR

International Inventories

All the substances contained in this product are listed or exempted from listing in the following inventories:
Canada (DSL/NDSL)
U.S.A. (TSCA)

Version HGHS



SDS # : 087443

FLUIDMATIC MV LV

Date of the previous version: 2017-09-14

Revision Date: 2017-09-14

Version 1

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health Hazard 1	Flammability 1	Instability 0	Special hazards -
HMIS	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

Revision Date: 2017-09-14
Revision Note Initial Release

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

NTP = National Toxicology Program

Section 8

TWA - Time Weight Average

STEL - Short Term Exposure Limits

+	Sensitizer	*	Skin designation
C:	Carcinogen	R:	Toxic to reproduction
Ceiling:	Ceiling Limit Value		

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

Version HGHS