

SAFETY DATA SHEET

According to Canadian Hazardous Products Regulations (HPR) (SOR/2015/17)

SDS #: 088189 RUBIA OPTIMA 1500 5W-40

Date of the previous version: not applicable **Revision Date:** 2018-07-07 **Version** 1

1. IDENTIFICATION

Product identifier

Product name RUBIA OPTIMA 1500 5W-40

Other means of identification

Product Code(s) 088189

Number GWO Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Engine oil

Uses advised against Do not use for any purpose other than the one for which it is intended.

Details of the supplier of the safety data sheet

Supplier TOTAL CANADA INC.

220, LAFLEUR LASALLE, QUEBEC

H8R 4C9

Tel: (514) 595-7579 Fax: (514) 595-5950

Contact Point service HSE

E-mail Address ProductSafety@total.com

Emergency telephone number

Emergency telephone 1-800-463-3955

Company Phone Number +1 866 928 0789 (24h/24, 7d/7) +1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation - Category 3

Label elements

Hazard Statements

Causes mild skin irritation



Date of the previous version: not applicable Revision Date: 2018-07-07 Version 1

Precautionary Statements - Response

Skin

If skin irritation occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Mixture</u>

Chemical nature Mineral oil of petroleum origin.

Chemical Name	EC-No	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	265-157-1	64742-54-7	50<60
Distillates (petroleum), solvent-dewaxed heavy paraffinic	265-169-7	64742-65-0	10<20
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated	605-315-2	163149-28-8	3<5
Reaction products of 1-decene, hydrogenated	-	68649-12-7	3<5
10-ethyl-12-heptyl-11,13-dimeth yltricosane; 8-ethyl-9,11-dimethyl-10-nonyln onadecane		151006-60-9	3<5
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyp henyl)propionate	406-040-9	125643-61-0	1<3
bis(nonylphenyl)amine	253-249-4	36878-20-3	1<3
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	298-577-9	93819-94-4	1<2.5
Molybdenum polysulphide long chain alkyl dithiocarbamate	457-320-2	۸	0.1<0.25



Date of the previous version: not applicable **Revision Date:** 2018-07-07 **Version** 1

complex

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while

rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration. Inhalation of high concentrations of vapor or aerosols

may cause irritation of the upper respiratory tract.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or Poison Control Center immediately. If swallowed,

do not induce vomiting - seek medical advice.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device. Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Skin contact Causes mild skin irritation. May produce an allergic reaction.

Eye contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Symptoms No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.



Date of the previous version: not applicable Revision Date: 2018-07-07 Version 1

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion

products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S.

Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Zinc oxides.

Explosion Data

Sensitivity to Mechanical Impact Sensitivity to Static Discharge None.

Special protective equipment for

fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General InformationDo not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water

courses.

Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or

similar non-combustible materials.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Keep in suitable, closed containers for

disposal. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according

to local / national regulations (see section 13).

7. HANDLING AND STORAGE



SDS #: 088189

RUBIA OPTIMA 1500 5W-40

Date of the previous version:not applicableRevision Date:2018-07-07Version 1

Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe

vapors or spray mist. Avoid contact with skin, eyes and clothing. When using, do not eat,

drink or smoke.

Prevention of fire and explosion Take precautionary measures against static discharges.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before

breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product

contaminated rags into workwear pockets. Use personal protective equipment as required. Avoid breathing vapors, mist or gas. Do not wash off with:. Fuel. Solvent. Abrasive. Avoid extended and repeated contact with the skin as this may cause skin conditions, which may also be aggravated by minor injuries or by contact with soiled clothing. Avoid prolonged and

repeated contact with the skin, especially with used or waste product.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture. Protect from frost, heat and

sunlight. Keep in properly labeled containers.

Materials to Avoid Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m³ (highly refined).

Legend See section 16

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits. Ensure

adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the



Date of the previous version: not applicable **Revision Date:** 2018-07-07 **Version** 1

recommended equipment.

Individual protection measures, such as personal protective equipment

General Information Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE)

recommendations apply to the product ITSELF. In case of mixtures or formulations, it is

suggested that you contact the relevant PPE suppliers.

Eye/face protection If splashes are likely to occur, wear safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. Please observe the

instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protectionNone under normal use conditions. When workers are facing concentrations above the

exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapor/particulate. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations

governing their choices and uses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Appearance limpid

Color No information available

Physical State @20°C liquid

Odor Characteristic

Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks</u> <u>Method</u>

pHMelting point/rangeNo information available

Boiling point/boiling range

No information available

Flash point >= 225 °C No information available ASTM D 92

>= 437 °F ASTM D 92.

Evaporation rate No information available

Flammability Limits in Air



Date of the previous version: not applicable Revision Date: 2018-07-07 Version 1

upperNo information availableLowerNo information available

Vapor PressureNo information availableVapor densityNo information available

 Relative density
 0.875
 @ 15 °C
 ASTM D1298

 Density
 875 kg/m³
 @ 15 °C
 ASTM D1298

Water solubility Insoluble

Solubility in other solvents

No information available
logPow

No information available

Autoignition temperature Not applicable

Decomposition temperatureNo information available

 Viscosity, kinematic
 86 mm2/s
 @ 40 °C
 ASTM D445

 14.4 mm2/s
 @ 100 °C
 ASTM D445

Explosive properties Not explosive Oxidizing Properties Not applicable

Possibility of hazardous reactions None under normal processing

Other information

Freezing Point No information available

10. STABILITY AND REACTIVITY

Reactivity None under normal processing.

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of hazardous reactions
No dangerous reaction known under conditions of normal use. None under normal

processing.

Conditions to avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Take

precautionary measures against static discharges. Strong oxidizing agents.

<u>Incompatible materials</u> Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides (

SO2 and SO3) and Hydrogen sulphide H2S. Zinc oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Symptoms No information available.

Skin contact Causes mild skin irritation. May produce an allergic reaction.

Eye contact Not classified based on available data.



Date of the previous version:not applicableRevision Date: 2018-07-07Version 1

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Oral Not classified based on available data

Dermal Not classified based on available data

Inhalation Not classified based on available data

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5.53 mg/l (aerosol) (rat - OECD 403)
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated 163149-28-8	LD50 5000 mg/kg bw (rat - OECD 403)	LD50 2000 mg/kg bw (rat - OECD 402)	
Reaction products of 1-decene, hydrogenated 68649-12-7	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rabbit - OECD 402)	LC50 (4h) > 5000 mg/m³ (Rat - Aerosol - OECD 403)
10-ethyl-12-heptyl-11,13-dimethyltri cosane; 8-ethyl-9,11-dimethyl-10-nonylnona decane 151006-60-9	LD50 5000 mg/kg bw (rat)	LD50 2000 mg/kg bw (rat - OECD 402)	LC50(4h) 5mg/L (rat - OECD 403)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphen yl)propionate 125643-61-0	LD50 > 2000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
bis(nonylphenyl)amine 36878-20-3	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4	LD50 2600 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit - OECD 402)	LC50(1h) > 2 mg/l (Rat - OECD Test Guideline 403)
Molybdenum polysulphide long chain alkyl dithiocarbamate complex ^	LD50 > 2000 mg/kg (Rat - OECD 425)	LD50 > 2000 mg/kg (Rat - OECD 402)	



Date of the previous version: not applicable **Revision Date:** 2018-07-07 **Version** 1

Skin corrosion/irritation Irritating to skin.

Serious eye damage/eye irritation Not classified based on available data. The supplier of one or more of the components

contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, eye damage classification

is not required.

Respiratory or skin sensitization Not classified based on available data. Contains sensitizer(s). May produce an allergic

reaction.

Germ cell mutagenicity Not classified based on available data.

Carcinogenicity Not classified based on available data. During use in engines, contamination of oil with low

levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil

is thoroughly removed by washing with soap and water.

Reproductive toxicity

Target Organ Effects (STOT)

Not classified based on available data.

None known.

STOT - single exposure
STOT - repeated exposure
Aspiration hazard

Not classified based on available data.
Not classified based on available data.
Not classified based on available data.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute aquatic toxicity - Product Information

No information available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
Reaction products of 1-decene, hydrogenated 68649-12-7	EL50 (72h) > 1000 mg/l (WAF - Scenedesmus capricornutum - static - OECD 201)	LC50 (96h) > 1000 mg/l (WAF - Oncorhynchus mykiss - semi static)	EL50 (48h) > 1000 mg/l (WAF - Daphnia magna - static - OECD 202)	
10-ethyl-12-heptyl-11,13-dim ethyltricosane; 8-ethyl-9,11-dimethyl-10-non ylnonadecane 151006-60-9				EC50(16h) 10000 mg/L



SDS #: 088189

RUBIA OPTIMA 1500 5W-40

Date of the previous version:not applicableRevision Date:2018-07-07Version 1

reaction mass of isomers of:	, , ,	LC50 (96h) > 74 mg/l	EC50(24h) > 100 mg/l	
C7-9-alkyl	(Scenedesmus sp OECD	(Brachydanio rerio - semi	(Daphnia magan - OECD	
3-(3,5-di-trans-butyl-4-hydro	201)	static - OECD 203)	202)	
xyphenyl)propionate				
125643-61-0				
bis(nonylphenyl)amine	EC50 (72h) > 100 mg/l	LC50 (96h) > 100 mg/l	EC50 (48h) > 100 mg/l	
36878-20-3	(Desmodesmus subspicatus	(Brachyanio rerio - OECD	(Daphnia magna - OECD	
	- OECD 201)	203)	202)	
Zinc bis[O-(6-methylheptyl)]	EbC50 (96h) 2.1 mg/l	LC50 (96h) 4.5 mg/l	EL50 (48h) 5.4 mg/l Daphnia	
bis[O-(sec-butyl)]	Selenastrum capricornutum	Oncorhynchus mykiss	magna (OECD 202)	
bis(dithiophosphate)	(OECD 201)	(OECD 203)		
93819-94-4				
Molybdenum polysulphide	EC50 (72h) 14 mg/l		EL50 (48h) 50 mg/l (Daphnia	
long chain alkyl	(Selenastrum capricornutum	(Oncorhynchus mykiss -	magna - OECD 202)	
dithiocarbamate complex	- OECD 201)	OECD 203)	,	
^ .	ĺ	,		

Chronic aquatic toxicity - Product Information

No information available

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 64742-65-0		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Reaction products of 1-decene, hydrogenated 68649-12-7		NOELr(21d) 125 mg/l (Daphnia magna)		

Effects on terrestrial organisms

No information available.

Persistence and degradability

No information available

Bioaccumulative potential

Product Information No information available.



Date of the previous version: not applicable Revision Date: 2018-07-07 Version 1

logPow No information available

Component Information

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	-
Reaction products of 1-decene, hydrogenated 68649-12-7	5
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate 125643-61-0	9.2
bis(nonylphenyl)amine 36878-20-3	7.7
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4	0.9
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	5.1

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility

Air Loss by evaporation is limited

Water The product is insoluble and floats on water

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste from residues/unused

products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration. Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

TDG Not regulated



Date of the previous version: not applicable Revision Date: 2018-07-07 Version 1

DOT Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) (SOR/2015/17) and the Safety Data Sheet (SDS) contains all the information required by the HPR

International Inventories All the substances contained in this product are listed or exempted from listing in the

following inventories: Canada (DSL/NDSL) U.S.A. (TSCA)

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPAHealth Hazard0Flammability1Instability0Special hazards -HMISHealth Hazard0Flammability1Physical Hazard0Personal protectionX

Revision Date: 2018-07-07 Revision Note Initial Release

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x =Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level



Date of the previous version: not applicable **Revision Date:** 2018-07-07 **Version** 1

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

NTP = National Toxicology Program

Section 8

TWA - Time Weight Average

STEL - Short Term Exposure Limits

+ Sensitizer * Skin designation
C: Carcinogen R: Toxic to reproduction

Ceiling: Ceiling Limit Value

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet